

June 10, 2014

STANDARDS BULLETIN 2014-11

New Edition

Second Edition of CAN/ULC-S519

STANDARD FOR COTTON-SYNTHETIC PERCOLATING FORESTRY HOSE

ULC Standards is pleased to announce the release of the Second Edition of CAN/ULC-S519-14, Standard for Cotton-Synthetic Percolating Forestry Hose. This Standard has been approved by the ULC Standards Committee on Fire Protection Equipment and Systems and has been published under the date of June 2014.

CAN/ULC-S519-14 will be of interest to anyone who manufactures, distributes, uses, regulates or inspects cottonsynthetic percolating forestry fire hose.

This Standard applies to woven-jacketed, lined, cotton-synthetic percolating forestry hose which contain non-synthetic fibres of the size commercially known as 38 mm having a minimum service test pressure of 2070 kPa, suitable for use in forest fire suppression.

The Second Edition of this standard contains revisions to the friction loss test and requirements for lining including thickness: tensile and elongation; and ozone-exposure. Additionally, various editorial updates have been made throughout the text.

Should you require any additional information, please contact Mark Ramlochan at (613) 755-2729 Ext. 61422 or email: Mark.Ramlochan@ul.com.

This Second Edition Standard can be ordered for \$260.00 CAD (hard copy) or \$216.67 CAD (PDF) though our website at www.ulc.ca and selecting *ULC Standards*. Once at the *ULC Standards* page, select *Sale of ULC Standards Materials*.

Yours truly,

ULC STANDARDS

G. Rae Dulmage

Director, ULC Standards

Kar Librage