

File : CAN/ULC-S712.1  
ULC-S700A  
ULC G5.2  
CCF7

03 February 2017

## **STANDARDS BULLETIN 2017-04**

NEW EDITION

### **Second Edition of CAN/ULC-S712.1:2017**

#### **STANDARD FOR THERMAL INSULATION – LIGHT DENSITY, OPEN CELL SPRAY APPLIED SEMI-RIGID POLYURETHANE FOAM – MATERIAL SPECIFICATION**

ULC Standards is pleased to announce the publication of the Second Edition of CAN/ULC-S712.1, Standard for Thermal Insulation – Light Density, Open Cell Spray Applied Semi-Rigid Polyurethane Foam – Material Specification. This Standard has been approved by the ULC Standards Committee on Thermal Insulation Materials and Systems (S700A) and has been published under the date of January 2017.

This Standard specifies the physical property requirements and test methods to determine the material properties for light density, open cell spray applied semi-rigid polyurethane foam, used as a thermal insulation for building applications, whether applied on a building site or in a prefabrication (manufacturing) facility.

The changes in this Second Edition CAN/ULC-S712.1 include:

- Updates to the referenced publications;
- Removal of comparison report requirement; and
- Addition of thermal resistance labelling requirement.

This Standard can be ordered for \$160.00 CAN (Hardcopy) or \$135.00 CAN (PDF) from the ULC Standards website at <http://canada.ul.com/ulcstandards/>. Select *Sales of ULC Standards Materials* for further details.

If you require any additional information, please contact Kevin HF Wu at (613) 755-2729 ext. 61437 or by email at [Kevin.HF.Wu@ul.com](mailto:Kevin.HF.Wu@ul.com).

Yours truly,

ULC Standards



Mahendra Prasad  
Standards Operations Manager  
[Mahendra.Prasad@ul.com](mailto:Mahendra.Prasad@ul.com)



Kevin HF Wu  
Project Manager  
[Kevin.HF.Wu@ul.com](mailto:Kevin.HF.Wu@ul.com)