



31 August 2009

STANDARDS BULLETIN 2009-32

Second Edition CAN/ULC-S130-09

STANDARD METHOD OF TEST FOR IGNITION RESISTANCE OF LOOSE FILL INSULATION (CIGARETTE METHOD)

ULC is pleased to announce the publication of the Second Edition of CAN/ULC-S130-09, Standard Method of Test for Ignition Resistance of Loose Fill Insulation (Cigarette Method). This Standard has been approved by the ULC Committee on Fire Tests, and has been published under the date of August 2009.

This Standard applies to cellulose fibre loose fill thermal insulation suitable for indoor use in building construction within the temperature range of -60 to 90 °C.

Insulation material conforming to this Standard is suitable for pouring by hand or for blowing through specially designed equipment. When so specified by the manufacturer, a particular product may be suitable for both methods of application.

If you require any additional information, please contact Mary Sengaroun at (613) 755-2729 ext. 6215 or by email at Mary.Sengaroun@ca.ul.com.

This standard can be ordered for \$181.00 CAN (Hardcopy) from the ULC website at www.ulc.ca by clicking on Order Standards and Directories followed by selecting ULC Online Store.

Yours truly,

UNDERWRITERS LABORATORIES OF CANADA

G. Rae Dulmage

Director, Standards Department, Government Relations Office and Regulatory