



File: S703

November 26, 2009

STANDARDS BULLETIN 2009-42

Second Edition CAN/ULC-S703-09

STANDARD FOR CELLULOSE FIBRE INSULATION (CFI) FOR BUILDINGS

ULC is pleased to announce the publication of CAN/ULC-S703-09, the Second Edition of Standard for Cellulose Fibre Insulation (CFI) for Buildings. This Standard has been approved by the ULC Committee on Thermal Insulation Materials and Systems (S700A), and has been published with the date of November 2009.

This Standard specifies requirements for treated wood-based cellulose fibre intended for use as thermal insulation (*Cellulose Fibre Insulation, CFI*) in new and existing buildings within the temperature range of -60 °C to 90 °C.

This Standard describes general requirements for the material and additional requirements specific to the types of *CFI*. The types are specified as Type 1 and Type 2.

The methods used in this Standard to measure and describe the properties of materials, products or assemblies in response to heat and flame under controlled laboratory conditions do not describe or appraise the fire hazard or fire risk of materials and products under actual fire conditions. Results of these tests are meant to be used as elements in a fire risk assessment that takes into account all of the factors that are pertinent to an assessment of the fire hazard of a particular end use.

If you require any additional information, please contact John Wade at 613-755-2729 ext. 6226 or by email at: John.Wade@ca.ul.com

This standard can be ordered for \$222.00 CAN (Hardcopy) from the ULC website (www.ulc.ca) ULC online store.

Yours truly,

UNDERWRITERS LABORATORIES OF CANADA

G. Rae Dulmage

Director, Standards Department, Government Relations Office and Regulatory