



July 30 2010

STANDARDS BULLETIN 2010-14

Second Edition CAN/ULC-S112.1-10

STANDARD FOR LEAKAGE RATED DAMPERS FOR USE IN SMOKE CONTROL SYSTEMS

ULC Standards is pleased to announce the publication of the Second Edition CAN/ULC-S112.1-10, Standard for Leakage Rated Dampers for Use in Smoke Control Systems. This Standard has been approved by the ULC Standards Committee on Fire Tests and has been published under the date of July 2010.

The requirements in this Standard cover dampers intended for use in heating, ventilating and air conditioning (HVAC) systems.

Leakage-rated dampers (smoke dampers) are intended to restrict the spread of smoke in HVAC systems that are designed to control the movement of smoke within a building when the HVAC system is operational in engineered smoke control systems.

Combination Fire and Smoke Dampers are intended to restrict the spread of smoke in HVAC systems that are designed to control the movement of smoke within a building when the HVAC system is operational in engineered smoke control systems, and provide a barrier to passage of flame and hot gases. Combination Fire and Smoke Dampers shall meet the requirements of CAN/ULC-S112, Standard Method of Fire Test of Fire-Damper Assemblies and this Standard.

If you require any additional information, please contact Mary Huras at (613) 755-2729 ext.6215 or by email at Mary.Huras@ca.ul.com.

This Standard can be ordered for \$193.20 CAN (Hardcopy) from the ULC website at www.ulc.ca by clicking on the ULC Standards logo and then click on Sales of ULC Standards Materials followed by selecting ULC Online Store.

Yours truly,

ULC STANDARDS

G. Rae Dulmage
Director, Standards Department, Government Relations Office and Regulatory