



March 11, 2011

STANDARDS BULLETIN 2011-08

New Edition to Standard

First Edition of CAN/ULC-S518.1-11

STANDARD FOR SYNTHETIC NON-PERCOLATING FORESTRY HOSE

ULC Standards is pleased to announce the release of the Second Edition of CAN/ULC-S518.1-11, Standard for Synthetic Non-Percolating Forestry Hose. This Standard has been approved by the ULC Committee on Fire Protection Equipment and Systems.

CAN/ULC-S518.1-11 will be of interest to anyone who manufactures, distributes, uses, regulates or inspects synthetic non-percolating forestry hose. This Standard applies to 25 and 38 mm synthetic percolating type hoses having a minimum service test pressure of 2070 kPa suitable for use in forest fire suppression. These hoses are classified as follows:

Class A — woven jacketed synthetic fibre with an integral lining; and

Class B — rubber covered jacket and rubber lined.

The Second Edition of this Standard has been revised to update sections on construction, requirements for finished hose, and requirements for lining. Additionally, various editorial updates have been made throughout the text. Should you require any additional information, please contact Mark Ramlochan at (613) 755-2729 Ext. 61422 or email: Mark.Ramlochan@ca.ul.com.

This First Edition of this National Standard of Canada can be ordered for \$184.80 through our website at www.ul.com/canada and selecting *ULC Standards*. Once at the *ULC Standards* page, select *Sales of ULC Standards Materials*.

Yours truly,

ULC STANDARDS

G. Rae Dulmage
Director, Standards Department, Government Relations Office and Regulatory