

File: S656 S600L ULC G5.2 CCF7

18 August 2014

## **STANDARDS BULLETIN 2014-25**

**NEW EDITION** 

## Second Edition of CAN/ULC-S656-14

## **Standard for Oil-Water Separators**

ULC Standards is pleased to announce the publication of the Second Edition of CAN/ULC-S656-14, Standard for Oil-Water Separators. This Standard has been approved by the ULC Standards Committee on Oil-Water Separators and has been published under the date of August 2014.

This Standard provides minimum requirements for shop fabricated single-wall or double-wall oil-water separators intended to collect and separate free oil from water by gravity separation at an inlet free oil concentration not exceeding 2 000 mg/L. These oil-water separators are also installed for the capture and retention of oil spills under dry weather conditions up to the free oil retention capacity of the oil-water separator. These oil-water separators are intended for installation and operation in accordance with, but not limited to, the following:

- A. Manufacturer's instructions;
- B. CCME Environmental Code of Practice for Aboveground and Underground Storage Tank Systems Containing Petroleum and Allied Petroleum Products;
- C. CPPI Code of Practice for Management of Water Effluent Quality at Petroleum Storage and Distribution Facilities; and
- D. Regulations of the authority having jurisdiction.

Changes to this Edition include an expanded Scope and modified testing methods to recognize alternate compliance routes.

If you require any additional information, please contact John Wade at 613.755.2729 ext. 61426 or by email at John.Wade@ul.com.

This Standard can be ordered for \$270.00 CAN (Hardcopy) or \$225.00 CAN (PDF) from the ULC Standards website at <a href="www.ulc.ca">www.ulc.ca</a> and select *ULC Standards*. Once on the ULC Standards homepage, select *Sales of ULC Standards Materials* for further details.

Yours truly,

**ULC Standards** 

G. Rae Dulmage

Director, Standards Department

J Kae Zumage